Battery - EV12226 / 6-DCM-26 / 6-DZM-26 / 6-FM-26, AGM, 12V 26Ah, Yimatzu - BATEV1226 - PBC94GF1



Rating: Not Rated Yet **Price**

\$87.31

Ask a question about this product

Description

Yimatzu 6-DCM-26 (also referred to as 6-DZM-26, EV12226, 6-EVF-26 and 6-FM-26) Sealed Lead Acid (SLA), Mai ntenance Free (MF), AGM class, specialized GEL electrolyte, 12V, 26Ah battery. This is the highest grade o f DCM/DZM battery produced by Yimatzu and continues to rank as the top performing DCM battery in the Globa l marketplace.

Yimatzu 6-DCM-26 is currently considered the most energy dense lead acid electric scooter/mobility/device battery in north america to fit within the most popular 181x77x170 millimeter (7.12x3.03x6.69 inches) case dimensions.

Yimatzu AGM (Absorbent Glass Mat) technology introduces the advantage of suspending the electrolyte within

an internal glass mat structure. This significantly reduces risk of vapour leak and provides substantiall y higher power capacity, increasing both total life span as well as the range of each individual cycle.

Yimatzu AGM series batteries provide a virtually maintenance free and risk free power solution by self-con taining the acidic electrolyte. This is crucial for vehicles where impacts can occur, such as powersports, mobility and watersports. Yimatzu AGM battery design will maintain its performance and long-term storage characteristics for several times longer than a conventional lead battery.

Yimatzu GEL electrolyte technology provides a safer battery with higher performing deep cycle characterist ics; greater cycle length and battery life-span. Yimatzu GEL impact and vibration dampening properties inc rease battery durability while providing superior resistance to temperature fluctuations and extremes. Yim tazu GEL ensures uniform electrolyte suspension, even plate discharge profiles, higher material heat capac ity and top rated leak proofing from both evaporation and battery impact.

It is the combination of these two technology types along with industry leading manufacturing systems whic h allow Yimatzu to produce an unrivaled DCM battery and deliver them worldwide at a lower cost to the cons umer. A finished product which provides the high power capacity and unmatched life expectancy of the Yimat zu AGM series, along with the improved deep cycle performance, stabilized discharge profile, advanced leak proofing and extended battery life of Yimatzu GEL electrolyte technology.

Note that a Yimatzu AGM battery with GEL electrolyte is different and far superior in almost every applica tion than a GEL cell battery. GEL cell batteries are typically more expensive with less forgiving recharge protocols and do not offer the same power capacity as their size-comparable AGM counterparts. GEL cell ba tteries occupy a very small percentage of the total market and should only be used when specifically direc ted by the manufacturer; typically when low power is required at a slow discharge rate.

This 6-DCM-26 battery type is most commonly used within the powersport, transportation, medical and power supply industries. Often (though not exclusively) used for on-road scooters, mopeds, mobility scooters and electric wheelchairs as well as a wide assortment of electric ATVs, dirt bikes, golf carts and other powe rsports, mobility or toy products in 12 volt intervals (12V, 24V, 36V, 48V, 60V, 72V, 84V and 96V primaril y).

Approximate Dimensions:

Length: 18cm (7.09in) Width: 7.7cm (3.03in) Height: 17cm (6.69in) Weight: 7.8kg (17.21bs) Terminals (centre to centre): 12cm (4.72in)